

according to Regulation (EC) No 1907/2006

	Micr	oDon H- Tec-			
Print date: 19.04.2017	Prod	uct code: 20-200_EN	1		Page 1 of 9
SECTION 1: Identification of	the substance/	mixture and of the	e company	/undertaking	
1.1. Product identifier MicroDON H-Tec	International	Nomenclature	Code	29 16 1400	
Product group:	Liquid compon	ent			
1.2. Relevant identified uses of	the substance o	r mixture and uses	advised aga	ainst	
Use of the substance/mixtur Creation of dental products	5				
1.3. Details of the supplier of the					
Company name:	Micropolymer Via Torrette Ba				
Street:		.S.Andrea Delle Frat	te		
Place:	06132 Perugia	(Italy)			
Telephone:	+39 32745725	61			
e-mail:		ymerdental.com			
Contact person:	Ing.Libero Leo				
e-mail:		ymerdental.com			
Internet:	www.micropoly	merdental.com			
1.4. Emergency telephone	+39026610102	29			
<u>number:</u>					
SECTION 2: Hazards identif					
2.1. Classification of the subst					
Regulation (EC) No. 1272/200 Hazard categories:	8				

Hazard categories: Flammable liquid: Flam. Liq. 2 Skin corrosion/irritation: Skin Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1 Specific target organ toxicity - single exposure: STOT SE 3 Hazard Statements: Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling Methyl methacrylate

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Precautionary statements P210 Kee

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No



according to Regulation (EC) No 1907/2006

	MicroDon H-Tec-	
Print date: 19.04.2017	Product code: 20-200_EN	Page 2 of 9
	smoking.	
P240	Ground/bond container and receiving equipment.	
P243	Take precautionary measures against static discharge.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to I	Regulation (EC) No. 1272/	2008 [CLP]	
80-62-6	Methyl methacrylate			95 - < 100 %
	201-297-1		01-2119452498-28	
	Flam. Liq. 1, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H224 H315 H317 H335			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.



according to Regulation (EC) No 1907/2006

MicroDon H-Tec-

Print date: 19.04.2017

Product code: 20-200_EN

Page 3 of9

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Dental prothesis

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL



according to Regulation (EC) No 1907/2006

MicroDon H-Tec-

Print date: 19.04.2017

Product code: 20-200_EN

Page 4 of 9

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
80-62-6	Methyl methacrylate			
Worker DNEL	, long-term	inhalation		208 mg/m³
Worker DNEL	, long-term	dermal		17 mg/kg bw/day

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	liquid colourless characteristic		
			Test method
pH-Value:		not determi	ned
Changes in the physical state			
Melting point:		-48	°C
Initial boiling point and boiling range:		100,5	°C
Flash point:		10	°C
Flammability Solid: Gas:		not applica not applica	
Lower explosion limits:		2,1 vo	I. %
Upper explosion limits:		12,5 vo	I. %
Ignition temperature:		421	°C
Auto-ignition temperature Solid:		not applica	able



according to Regulation (EC) No 1907/2006

			2000	& distribution srl
	MicroDo	on H- Tec-		
Print date: 19.04.2017	Product code	e: 20-200_EN		Page 5 of 9
Gas:		not ap	plicable	
Decomposition temperature:		not det	ermined	
Oxidizing properties Not oxidizing.				
Vapour pressure: (at 20 °C)			36 hPa	
Density (at 15,5 °C):		0,94	l9 g/cm ³	
Water solubility: (at 20 °C)			12,5 g/L	
Solubility in other solvents not determined				
Partition coefficient:			1,38	
Viscosity / dynamic: (at 20 °C)		0,53	3 mPa⋅s	
Vapour density: (at 20 °C)			3,5	
Evaporation rate:		not det	ermined	
9.2. Other information				
Solid content:		not det	ermined	
10.1. Reactivity Flammable, Ignition hazard. 10.2. Chemical stability The product is stable under stora 10.3. Possibility of hazardous reaction No known hazardous reactions. 10.4. Conditions to avoid Keep away from sources of heat explosive mixtures with air. 10.5. Incompatible materials No information available. 10.6. Hazardous decomposition procession	(e.g. hot surfaces), s ducts		es. Vapours can form	
No known hazardous decomposi	•			
SECTION 11: Toxicological inform				
11.1. Information on toxicological eff				
Toxicocinetics, metabolism and d The product has not been tested				
Acute toxicity Based on available data, the clas	ssification criteria are	not met.		
ATEmix tested				
	Dose	Species	Source	
LD50, oral	7870 mg/kg	Rat		
LD50, dermal	> 5000 mg/kg	Rabbit		



according to Regulation (EC) No 1907/2006

		1	microDon H-T	ec-		
Print date:	19.04.2017	Proc	duct code: 20-2	00_EN		Page 6 of
LC5	0, inhalative (vapour) (4 h)	78 mg/l	Rat	t		
CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
80-62-6	Methyl methacrylate					
	oral	LD50	>5000 mg/kg	Rat	OECD 401	
	dermal	LD50	>5000 mg/kg	Rabbit		
	inhalative vapour	LC50	29,8 mg/l	Rat		

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Methyl methacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Methyl methacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Acute (short-term) fish toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose		[h] [d]	Species	Source
80-62-6	Methyl methacrylate					
	Acute fish toxicity	LC50	> 79 mg/l		Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50	> 110 mg/l	72 h	Selenastrum capricornutum	OECD 201
	Acute crustacea toxicity	EC50	69 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202
	Crustacea toxicity	NOEC	37 mg/l	21 d	Daphnia magna (Big water flea)	OECD 202

12.2. Persistence and degradability

Biodegradable.

12.3. Bioaccumulative potential

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	Methyl methacrylate	1,38

12.4. Mobility in soil Mobility in soil: No adsoption in soil or sediment.



according to Regulation (EC) No 1907/2006

	MicroDon H- Tec-	
7	Product code: 20-200 EN	

Page 7 of 9

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Other adverse effects

No information available.

Further information

Print date: 19.04.207

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

OLOTION 14. Transport information	
Land transport (ADR/RID)	
14.1. UN number:	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Transport category:	2
Hazard No:	339
Tunnel restriction code:	D/E
Other applicable information (land tr	ansport)
E2	
Inland waterways transport (ADN)	
14.1. UN number:	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es):	3
14.4. Packing group:	I
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Other applicable information (inland	waterways transport)
E2	
Marine transport (IMDG)	
14.1. UN number:	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es):	3



according to Regulation (EC) No 1907/2006

MicroDon H-Tec-		
Print date: 19.04.2017	Product code: 20-200_EN Page 8 of 9	
14.4. Packing group:	11	
Hazard label:	3	
Special Provisions:	-	
Limited quantity: EmS:	1 L F-E, S-D	
Other applicable information (marine transport) E2		
Air transport (ICAO)		
14.1. UN number:	UN 1247	
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	II	
Hazard label:	3	
Limited quantity Passenger:	1 L	
IATA-packing instructions - Passenger:		
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo:	5 L 364	
IATA-max. quantity - Cargo:	60 L	
Other applicable information (air transport) E2 Passenger-LQ: Y341		
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS: no		
14.6. Special precautions for user Warning: Combustible liquids.		
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code		
not applicable		
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		
EU regulatory information		
Additional information		
To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC		
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.	
Water contaminating class (D): Skin resorption/Sensitization:	1 - slightly water contaminating Causes allergic hypersensitivity reactions.	
15.2. Chemical safety assessment		
Chemical safety assessments for substances in this mixture were not carried out.		
SECTION 16: Other information		

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route European Agreement concerning the International Carriage of Dangerous Goods by Road)



according to Regulation (EC) No 1907/2006

microDon H-Tec-

Print date: 19.04.2017

Product code: 20-200_EN

Page 9 of 9

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

- Extremely flammable liquid and vapour. H224
- Highly flammable liquid and vapour. H225 Causes skin irritation. H315 May cause an allergic skin reaction. H317
- H335 May cause respiratory irritation.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our presentday knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)